

Sorts	Type	Parameters
System	Operating system	Linux
	Online visitor	Supports 4 visitors viewing at the same time.
	APP	O-KAM Pro
Collection	CPU	Sigmastar 335
	Memory	512Mb
	Lens	4mm F1.0
	Image sensor	1/2.9 CMOS sensor
	Minimum illumination	0.01Lux
	Sensor performance	Supports automatic white balance, automatic gain control, and automatic backlight compensation.
	Night vision	Color night vision
	Viewing angle	Diagonal: 91 °, horizontal: 77.3 °, vertical: 42.9 °
Video	Resolution	2304*1296P/25FPS/3 MP
	Compression standard	H.264+ /H.264 /MJPEF/JPEG
	IR control	No IRCUT, full-color night vision
	Bit rate	128 ~ 4096kbps
	Image adjustment	Brightness, contrast, OSD display
Audio	Input	Built-in-38dB microphone
	Output	Built-in 8Ω2W speaker
	Sampling frequency/bit width	8KHz/16bit
	Compression standard/Bit Rate	G711A
AI	Humanoid detection	Humanoid detection, filtering invalid alarm events.
	Area detection	Customize detection zones, only monitor areas that matter.
	Intelligent notification sound	Set different notification sounds for different devices, so that you can accurately determine which device is triggered.
	Intelligent alarm sound	Set different alarm sounds based on different scenarios.
	Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc.

Network	4G(China)	FDD:B1/B3/B5/B8
		TDD:B34/B38/B39/B40/B41
		WCDMA:B1/B5/B8
	4G(Europe)	FDD: B1/B3/B5/B7/B8/B20
		TDD:B38/B40/B41
		WCDMA: B1/B5/B8
Storage	External TF card	Supports T-Flash cards (up to 256GB)
	Cloud storage	Support cloud storage, users can purchase according to their needs.
Alarm	Alarm detection	Supports motion detection, human detection, human framing,siren alarm, and area detection
Physical Indicators	Rated voltage	DC5V±5%
	Power consumption	Power:/W Maximum power:/8W
	Operating condition	Temperature: -10 ~ 55°C; Humidity: < 90%
	Weight	Gross weight: (Note: in kind prevail)
	What's in the box	Camera, screw pack, warning sticker, screwdriver, manual