

| ★ Resolution 200W | | |
|--|-------------------------------|--|
| ★ Three views, monitor with no blind spots | | |
| ★ F2.0 large aperture, more light inputs, clearer night vision | | |
| ★ ISP image processing technology, preserving true colors | | |
| ★ Human detection, real time alerts | | |
| Sorts | Type | Parameters |
| System | Operating system | Linux |
| | Online visitor | Supports 4 visitors at the same time |
| | APP | O-KAM Pro |
| Collection | CPU | Ingenic |
| | Memory | 512Mb |
| | Lens | 4mm |
| | Image sensor | 1/2.7 inch 1080p progressive scan CMOS sensor |
| | Min. Illumination | 0.5Lux (color mode), 0.1Lux (b&w mode) |
| | Sensor performance | Support automatic white balance, automatic gain control and automatic backlight compensation |
| | Night vision | Black and white night vision, full-color night vision |
| | Viewing angle | D 91° |
| Video | Resolution | 2960*1665P/25FPS/500W |
| | Night vision | Black and white night vision, full-color night vision |
| | Compression standard | H.264 main profile/Motion-JPEG/JPEG |
| | IR control | IR-CUT, soft photosensitive control |
| | Bit rate | 128 ~ 4096kbps |
| | Image adjustment | Brightness, contrast, OSD display |
| Audio | Input | Built-in -38dB microphone |
| | Output | Built-in 8Ω1W speaker |
| | Sampling frequency/bit width | 8KHz/16bit |
| | Compression standard/Bit Rate | G711A |
| Pan/Tilt | Rotation angle | Pan: 270° Tilt: 90° |
| Network | Network interface | 10Mbps/100Mbps |
| | Network protocol | TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P |
| | Wireless network | IEEE802.11b/g/n |
| | Wireless frequency | 2.4G |
| | Wireless security encryption | 64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption |
| Storage | External TF card | Supports T-Flash cards (up to 256GB) |
| | Cloud storage | Support cloud storage, users can purchase according to their needs. |
| Alarm | Alarm detection | Motion detection, human detection, human framing, siren alarm, and area detection |
| Physical Indicators | Rated voltage | DC12V±12% |
| | Power consumption | |
| | Operating condition | Working temperature: -10~55 °C, working humidity<90% |
| | Weight | (Note: in kind prevail) |
| | Packing list | (Note: in kind prevail) |