

Model: C993

Sorts	Type	Parameters
System	Operating system	Embedded Linux
	Online visitor	Supports 4 visitors at the same time
	CPU/image sensor	1/4.5 inch high-quality 1 Mbps CMOS image sensor
	Minimum illumination	0.5 Lux(Color mode), 0.1 Lux(B&W mode)
	Lens/viewing angle	58.7°
	Night vision	Dual filter automatic switching, white light, illumination distance 5-10m
	Compression standard	H.264 main profile/Motion-JPEG/JPEG
	Data rate	Main stream: 1080p(1920×1080)@30fps/1296p(2304×1296)@15fps Substream: 360p(640×360)@15fps
	Bit rate/maximum frame rate	128~4096kbps/30fps
	Image adjustment	Flip up and down
Audio	Input	Built-in -38dB microphone
	Output	Built-in 8 Ω 1W speaker
	Sampling frequency/bit width	8KHz/16bit
	Compression standard/bit rate	G.711/64kbps
Network	Network interface	No
	Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2Petc.
	Wireless network	IEEE802.11b/g/n; Supports AP configuration and Bluetooth connection
	Wireless frequency	2.4~2.4835GHz
	Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
Pan&Tilt	Rotation angle	Horizontal 355 °/Vertical 60 °
	Preset position	Supports 16 presets (mobile app only supports 5)
Storage	Storage	Supports T-Flash card(max supports 256GB); Cloud Storage;NVR; NAS;
Alarm	Alarm detection	Supports motion detection, humanoid detection, human tracking, voice and flash alarm, illumination function, timing white light on/off
Physical indicators	Rated voltage	DC5V
	Power consumption	Rated 2W
	Operating condition	Temperature: -10~50C; Humidity: < 90%
	Weight	Camera:186g
	Package size	(Note: in kind prevail)